

# 20" Twin ScaleStick



## Standard features

Model	Filter Housing Head	Sump	O'Ring	Bracket	Screws
FA-SS-SD-TW-20	Black Polypropylene	Clear	noryl	Stainless Steel	Stainless Steel
FA-SS-CB-TW-20	Black Polypropylene	Clear	noryl	Stainless Steel	Stainless Steel

## System specifications

- Poids :17 lbs,
- Life Rate : 3,000 - 6,000 Gallons
- Maximum feed pressure :125 psi,
- Maximum feed temperature : 105°F,
- Protect from freezing,
- Flow Rate (GPM) : 2-6,
- Line size : 1/2" (15/21) ou 3/4" (20/27),
- 20 micron sediment prefiltration include (FA-SS-SD-TW) or 10 micron Carbon Block (FA-SS-CB-TW),
- 20" prefilter sump : blue.



## Applications

High flow rate & volume applications (2-6 gpm). Multiple steamer or combi-oven where usage is 6 hours plus per day. Multiple coffee, espresso, & tea machines. Hot water dispensers, bread proofers, & ice machines under 1600 lbs.



## Install

Twin

## Delivery

Ready to use in individual generic cardboard box  
Installation instructions include  
1/4 ball valves include  
wrench include

[Replacement cartridges for FA-SS-SD-TW : SD-20 & SS-10](#)

[Replacement cartridges for FA-SS-CB-TW : CB-20 & SS-10](#)