

# 10" Twin ScaleStick



## Standard features

Model	Filter Housing Head	Sump	O'Ring	Bracket	Screws
FA-SS-SD-TW	Black Polypropylene	Clear	noryl	Stainless Steel	Stainless Steel
FA-SS-CB-TW	Black Polypropylene	Clear	noryl	Stainless Steel	Stainless Steel

## System specifications

- Poids : 11 lbs,
- Life rate : 3 000 - 6 000 Gallons,
- Maximum feed pressure : 125 psi,
- Maximum feed temperature : 105 °F,
- Protect from freezing,
- Flow rate (GPM) : 1-4,
- Line size : 1/2" (15/21) or 3/4" (20/27),
- 20 micron sediment filtration include (FA-SS-SD-TW) or 10 micron Carbon Block (FA-SS-CB-TW),

## Applications

Moderate flow rate & volume applications (1-4 gpm). Individual steamer or combi-oven where usage is 6 hours plus per day. Multiple coffee, espresso, & tea machines. Hot water dispensers, bread proofers, & ice machines under 800 lbs.



## Install

Twin

## Delivery

Ready to use in individual generic cardboard box  
Installation instructions include  
1/4 ball valves include  
wrench include

Replacement cartridge for FA-SS-SD-TW : SD-10 & SS-10

Replacement cartridge for FA-SS-CB-TW : CB-10 & SS-10

